INTENTIONALLY
LEFT BLANK

INTENTIONALLY
LEFT BLANK

INTENTIONALLY
LEFT BLANK

INTENTIONALLY
LEFT BLANK

INTENTIONALLY
LEFT BLANK

INTENTIONALLY
LEFT BLANK



SERVICING AREAS

The optimum servicing area provides the best access to the ATM for all servicing and operation tasks.

Wherever possible the ATM should be installed within the optimum servicing area.

If the optimum area is not available then refer to Servicing Areas - Minimum. However note that installing the ATM in the minimum servicing area may increase the servicing and/or upgrading time over a ATM installed using the optimum area.

Always leave as much space as possible around the ATM to facilitate safe operation and servicing.

Optimum

Minimum

NCR Proprietary Information - not to be disclosed or reproduced without written consent. © 2016 by NCR Corporation, Duluth, Georgia, U.S.A. http://www.ncr.com. All Rights Reserved



PACKAGE DIMENSIONS

ATM DIMENSIONS

WEIGHT

Standard Security Enclosures

	CEN Grade 1
Maximum weight	983 kg (2167.1 lb.)
Floor loading	1596 kg/m² (326.8 lb./ft²)

ISLAND DIMENSIONS AND BOLLARD LOCATIONS

The illustration below shows the dimensions for the minimum island size.

NCR recommends that the rear bollards are **102 mm** (4.0 in.) in diameter, and positioned in line with the rear of the ATM, front bollards are **102 mm** (4.0 in.) in diameter and positioned **25.4 mm** (1.0 in.) back from the front of the island.

When locating the bollards allow sufficient working space for servicing the air conditioning unit.

Anti-theft Bollards

If anti-theft bollards (also known as anti lassoing bollards) are to be fitted, the bollard exclusion zone around the ATM must be complied with to allow sufficient access for removing panels, refer to the Servicing Areas section.

NCR Proprietary Information - not to be disclosed or reproduced without written consent. © 2016 by NCR Corporation, Duluth, Georgia, U.S.A. http://www.ncr.com. All Rights Reserved



SECURITY BOLTS

The island, or base, must be capable of withstanding the loading imposed by the anchor points for the bolts. Bolts and anchors must be supplied by the owning organisation.

To ensure conformity to EN1143-1 Anchoring Strength Test, it is recommended that the ATM is bolted to the island, or base, through all six of the security enclosure bolt holes, using bolts with anchor washers as specified below. Bolts and anchor washers are to be supplied by the owning organisation.

Make sure that the island, or base, is capable of withstanding the loading imposed by the anchor points for these bolts.

If an adjustable plinth is used, it must be bolted to the island, or base, to the same specification as the ATM.

The minimum specification for bolts and washers to secure the ATM is:

- Bolts
  - Type - either resin anchor or shield anchor bolts
  - Size - **M16** (5/8 in.)
  - Minimum Length - **150 mm** (5.9 in.)
  - Strength - high tensile (minimum ISO property class **8,8**).
- Washers
  - Type - flat, steel (as per DIN7349 or equivalent)
  - Size - **M16** (5/8 in.)
  - Outer diameter - no greater than **40 mm** (1.58 in.)
  - Minimum thickness - **6 mm** (0.2 in.).

BOLT HOLES

The ATM should be bolted to the floor or plinth, through the holes marked 'A', using the six bolts with anchor washers.

The hole marked 'B' enables a security sensor to be fitted.

CABLE ENTRY

Cables enter the ATM through a hole in the base of the security enclosure. There should be a conduit hole in the island of sufficient size to allow the cables to be coiled ready to be brought into the security enclosure.

Make sure that the island conduit hole is free from any material that may impede the cables. The hole should not be sealed or filled with concrete.

The actual conduit hole may be larger than the that shown depending on the installation.

Distribution boxes and any power and wiring conduits must not protrude above the surface of the island.

ATM Cable Entry

CEN Security Enclosure

NCR Proprietary Information - not to be disclosed or reproduced without written consent. © 2016 by NCR Corporation, Duluth, Georgia, U.S.A. http://www.ncr.com. All Rights Reserved

ITM: NCR SELFSERV 88 ATM

DESIGN, INC.

ARCHITECTURE PLANNING INTERIOR DESIGN

15810 PARK TEN PLACE, SUITE 300
HOUSTON, TEXAS 77084
713-465-4650
www.sligroup.com

© COPYRIGHT

Neches FCU - Little Cypress ITM
7125 HWY 87 N
ORANGE, TX 77630

Project Number : 8976

	DATE
ISSUED FOR CLIENT APPROVAL	02.20.2026
ISSUED FOR BIDDING	03.03.2026
ISSUED FOR PERMIT	03.03.2026
ISSUED FOR CONSTRUCTION	

REVISIONS

MARK	DESCRIPTION	DATE

The information, ideas, designs, details, layouts, techniques, features, arrangements, plans, sequences, dimensions, allowances, tolerances, conceptions, specifications, intentions, technology or embodiments, as illustrated, arranged, displayed, noted, recorded, indicated, represented, disclosed, evidenced, detailed or otherwise reduced to tangible form hereon, either expressly, inherently or by implication, are the confidential and proprietary information of SLI Design, Inc., and shall not be used for any purpose other than the specific project or undertaking identified on the drawing title block or legend for which they are and have been prepared by SLI Design, Inc. Any other reproduction, disclosure or use of any portion of the confidential and proprietary information of SLI Design, Inc., shall be a breach of the obligation of confidence created by the acceptance of this drawing from SLI Design, Inc. for a specific project or Contract. Any copying, duplicating, reproducing, utilization, alteration, modification, revision or change to this drawing, is expressly prohibited unless done with the prior written consent or approval of SLI Design, Inc., and shall not be undertaken without receipt of such prior written approval. This drawing is loaned by SLI Design, Inc., for the limited purpose of complying with a specific Contract. The drawing remains the property of SLI Design, Inc., and shall be returned upon request or completion of the contract, unless specifically authorized by Contract, under which it was loaned.

PRINT DATE: 3/3/2026 12:10:40 PM



03/03/2026

DRAWING TITLE
BANK EQUIPEMENT

DRAWN BY	RG	SHEET NO.
CHECKED BY	BL	SP-2.20
APPROVED BY	TB	

X:\Neches FCU - Little Cypress ITM\Drawings\Revit\Neches FCU - Little Cypress ITM__V26_251204.rvt